

## LEAD AND COPPER REDUCED MONITORING SITE PLAN

Facility Number: \_\_\_\_\_ Facility Name: \_\_\_\_\_

List 30 sites from the original sampling pool to be used for the reduced monitoring pool. Sites must be chosen as follows:

1. The lead/copper rule requires a facility to always use the highest available Tier sites first. In other words, all Tier 1 sites (i.e., P1C, P1A, P1D) sampled in the first two rounds of monitoring must be sampled during reduced monitoring before Tier 2 sites may be sampled. Likewise all active Tier 2 sites must be sampled before Tier 3 sites may be sampled.
2. Primary sites are preferred. However, previously approved alternates may be used if enough primary sites are not available.
3. If your facility has lead service lines, you should maintain the same mix of Tier Type A and Tier Type C that was sampled in the original sample pool. At no time should there be less than 50% Tier Type C, unless all the active Tier type C sites are already included in the reduced monitoring sampling pool.
4. All Tier Type S must be sampled before Tier Type R may be sampled.

**If sites are not chosen as outlined above, results will not be used to calculate compliance and your supply will receive a monitoring violation.**

Please list sites in numerical order (P1A001, P1A002, P3S003, etc.)

1.		11.		21.	
2.		12.		22.	
3.		13.		23.	
4.		14.		24.	
5.		15.		25.	
6.		16.		26.	
7.		17.		27.	
8.		18.		28.	
9.		19.		29.	
10.		20.		30.	

Mail this form **after collection of samples** to: **IEPA/BOW/CAS #19**  
**P.O. Box 19276**  
**Springfield, IL 62794-9276**