LEAD AND COPPER REDUCED MONITORING SITE PLAN

Facility Number:	Facility Name:	

List five sites from the original sampling pool to be used for the reduced monitoring pool. Sites must be chosen as follows:

- 1. The lead/copper rule requires a facility to always use the highest available Tier sites first. In other words, all Tier 1 sites (i.e., P1C, P1A, P1D) sampled in the first two rounds of monitoring must be sampled during reduced monitoring before Tier 2 sites may be sampled. Likewise all active Tier 2 sites must be sampled before Tier 3 sites may be sampled.
- 2. Primary sites are preferred. However, previously approved alternates may be used if enough primary sites are not available.
- 3. If your facility has lead service lines, you should maintain the same mix of Tier type A and Tier Type C that was sampled in the original sample pool. At no time should there be less than 50% Tier Type C, unless all the active Tier type C sites are already included in the reduced monitoring sampling pool.
- 4. All Tier Type S must be sampled before Tier Type R may be sampled.

If sites are not chosen as outlined above, results will not be used to calculate compliance and your supply will receive a monitoring violation.

Please list sites in numerical order (P1A001, P1A002, P3S003, etc.)

1.	
2.	
3.	
4.	
5.	

Mail this form after collection of samples to:

IEPA/BOW/CAS #19 P.O. Box 19276 Springfield, IL 62794-9276

This Agency is authorized to require this information under III. Rev. Stat., 1989, Chapter 111 1/2, Section 1019. Disclosure of this information is required. Failure to do so may result in a civil penalty up to \$1,000.00 and an additional civil penalty up to \$1,000.00 each day the failure continued, a fine up to \$1,000.00 and imprisonment up to one year. This form has been approved by the Forms Management Center.