

AERIAL ASSESSMENT REPORT FOR Big and Little Muddy Rivers

Jackson County

November 2005

Prepared by Wayne Kinney for IL. Department of Agriculture

The Big Muddy River watershed TMDL final report list only segment N12 (Fig. 1) as impaired. This eight mile reach is impacted by manganese, sulfates, pH and DO. The TMDL report has determined the manganese and sulfates are potentially from groundwater contamination caused by abandoned coal mines and the likely source of the DO impairments in this reach is a lack of aeration caused by stagnant stream conditions and elevated in stream temperatures.




Fig. 1 Map of Aerial Assessment of Big and Little Muddy Rivers and TMDL Segment

Assessment Procedure

Low level geo-referenced video was taken of the Big and Little Muddy Rivers in March, 2004. Video taping was completed by Fostaire Helicopters, Sauget, IL, using a camera mounted beneath a helicopter to record data from just above tree top level in DVD format for further evaluation and assessment. Video mapping began near Sand Ridge where the Big Muddy enters the Mississippi River Bottoms approx. 4 miles southwest of Murphysboro, IL. The mapping progressed upstream to the confluence with the Little Muddy River east of De Soto, IL and then followed the Little Muddy River to a point

approximately 1 mile above the Jackson County line southeast of DuQuoin, IL. Aerial video of tributaries was not part of the project, regardless of the stream size or vegetation.

After videotaping the stream, the DVD tapes were processed by USGS to produce a geo-referenced DVD showing flight data and location. Next, USGS identified features from the video and created shapefiles containing the GPS location, type of feature identified, and the time on the DVD to allow cross referencing. The shape-files along with the DVD were then used to identify and locate the points where ground investigations were needed to verify aerial assessment assumptions and gather additional data.

The ground investigations or “ground truthing” is intended to accomplish two primary functions. First, it provides those viewing videos the opportunity to verify the correct interpretation of the video. Second, the video allows the user to identify and gather field data at the most appropriate locations to more closely represent the entire study portion of the stream.




Figure 2 Channel Profile of Big and Little Muddy River
(Profile begins at Elev. 330 near River Mile 68 on the Mississippi River.)

Detailed elevation data is not available; therefore the channel slope is calculated from USGS topo maps by measuring the channel length between contour lines. The report refers to this as “valley profile” although a true valley profile would use a straight line distance down the floodplain rather than channel length. However, this method is used because it incorporates sinuosity into the calculation and allows the channel slope to be assume equal to “valley slope” in order to estimate channel capacity, velocity, etc.,

although there are short segments where the channel slope may differ significantly near roads, logjams, knickpoints, etc.

CHAPTERS ON DVD AND ASSESSMENT REPORT Big and Little Muddy Rivers			
DVD Disc	DVD chapter	Beginning Time	Report Chapter
1	2	5:00	1
1	3	10:00	2
1	4	15:00:00	3
1	5	20:00:00	4
1	6	25:00:00	5
1	7	30:00:00	6
1	8	35:00:00	7
1	9	40:00:00	8
2	2	5:00	9
2	3	10:00	10
2	4	15:00:00	11
2	5	20:00:00	12
2	6	25:00:00	13
2	7	30:00:00	14
2	8	35:00:00	15

Fig. 3 DVD Chapters and Report Guide

The DVD has been divided into “chapters” of approximately five minutes of video (Fig. 3) to enhance the ability to navigate within the flight video and provide a simple way to identify and discuss different stream segments. Although the report will begin with a broader more general assessment of the entire study reach, it will also provide an assessment and treatment recommendations by chapter or group of chapters. The chapter divisions are clearly arbitrary and do not reflect “change points” in the stream characteristics or treatment recommendations. For clarity the conclusions and recommendations are presented for each stream “chapter”.

The major factors indicating channel conditions identified from the aerial assessment have been totaled by DVD chapter in Table 1 below. This tabulation allows a general comparison of the relative dominance of features found in each chapter and provides a means of comparing stream characteristic between chapters. A discussion of the major differences will follow later in this report.

FEATURES IDENTIFIED BY CHAPTER									
CHAPTER	ROCK OUTCROP	GEOTECH LOGJAM	FAILURE	DEPOSITION	BED CONTROL	BANK CONTROL	EROSION	SEVERE EROSION	BED STRUCTURE
1	0	0	0	0	0	0	18	0	0
2	0	1	1	0	0	0	8	0	0
3	0	0	3	0	0	1	18	0	0
4	0	0	3	0	0	0	16	1	0
5	0	0	7	0	0	0	16	0	0
6	0	0	3	0	0	0	17	0	0
7	1	1	0	0	0	0	26	0	0
8	2	0	2	0	0	0	19	0	0
9	5	2	3	2	0	0	18	0	0
10	0	0	5	0	3	0	20	0	2
11	1	2	3	0	0	0	31	0	0
12	0	0	1	0	1	0	15	0	0
13	0	1	0	0	1	0	26	0	0
14	0	2	0	0	0	0	35	0	2
15	0	4	0	0	0	0	11	0	0
TOTALS	9	13	31	2	5	1	294	1	4

Table 1 Features by Chapter Identified with Aerial Assessment

Chapters 1 through 6 are located on the Big Muddy River and Chapters 7 through 15 are on the Little Muddy River.

General Observations

1. The Big Muddy has a very low gradient at 0.186 ft/mi. as measured from the USGS topographic maps. In fact the profile which begins at elev. 330 is found in the Mississippi River near river mile 68 and contour line 340 is located on the Big Muddy near the Southern Illinois Airport between Murphysboro and U.S. Rte. 50, a distance of over 50 miles.
2. The Little Muddy River has more gradient, however it is still less than 1.0 ft. per mile through the entire reach of the aerial assessment.
3. Re-aeration of the Big and Little Muddy Rivers using in-stream structures is probably not feasible due to the low gradient preventing creation of significant turbulence to re-aerate the water.
4. Nutrient contributions from streambank erosion that may impact the algal growth and then potentially impact the DO seem to be low in comparison with other Illinois streams. The TMDL segment of N12 is primarily in Chapter 3 of the aerial assessment with 18 identified erosion sites. Adding the portions of Chapter 2 and 4 in N12 only increases the erosion sites to 26.
5. There is no appreciable point bar development in Big Muddy River and only in the Little Muddy does noticeable bar development occur. This lack of bar development along with the absence of significant woody debris from failed banks is an indication that the streambank erosion identified has a slower lateral movement than most Illinois streams.

6. There are 31 identified geotechnical failures in the study reach in addition to 294 erosion sites. Consideration of treatment at these sites should include use of Stream Barbs to trap sediment near the eroding banks and create the maximum turbulence possible at this gradient. Stream Barbs may be especially well adapted for sites with geotechnical failures by trapping sediment near the failed banks and thereby “loading the toe” to help resist future geotechnical failures.
7. No cross section were taken to develop “geomorphic bankfull” data, however it seems apparent that there is no incision occurring along the study reaches.
8. At the time of the aerial assessment flight there is a very noticeable difference in water clarity at the confluence with Crab Orchard Creek. This difference can be observed on DVD 1 at 30:22 or in Fig.
9. There are a series of manmade “riffles” in the Little Muddy River on DVD 2 at 11:20, 13:49 and 14:48 that do provide some re-aeration. However, the gradient in this reach is approx. 5 times that found in the TMDL segment N12.

Recommendations—Big Muddy River (Chapters 1 through 6)

The recommended treatment for this segment is to treat the identified erosion sites and geotechnical failure sites with a series of Stream Barbs. The result of treatment will be the redirection of flow toward the center of the channel causing some re-aeration to occur. The stream barbs will also trap sediment near the failed banks and stop the bank erosion while adding significant sediment which can help prevent future geotechnical failures.

Table 2 will provide an estimate of the length of bank treatment required and a preliminary cost.

TREATMENT CHAPTER 1-6 : Big Muddy River Lateral Bank Treatment with Stream Barbs					
Chapter	Geotech or Erosion Sites	Average Length	Total Length	Average Cost/foot	Total Cost
1	18	750	13500	\$75.00	\$1,012,500
2	9	750	6750	\$75.00	\$506,250
3	21	750	15750	\$75.00	\$1,181,250
4	19	650	12350	\$75.00	\$926,250
5	23	650	14950	\$75.00	\$1,121,250
6	20	650	13000	\$75.00	\$975,000
Total	110		76300		\$5,722,500

Table 2. Treatment needs for Chapter 1-6



Fig. 4 Geotechnical failure on DVD 1 at 7:29

Big and Little Muddy River-- Chapter 1




Fig. 5 Chapter 1

Big and Little Muddy River-- Chapter 2




Fig. 6 Chapter 2



Fig. 7 Bank Erosion in pastured area on DVD 1 at 17:15

Big and Little Muddy River-- Chapter 3




Fig. 8 Chapter 3

Big and Little Muddy River-- Chapter 4




Fig. 9 Chapter 4



Fig. 10 Geotechnical failure with mature tree standing vertically in channel on DVD 1 at 28:04



Fig. 11 Geotech failure next to farm pond on DVD 1 at 27:54

Big and Little Muddy River-- Chapter 5




Fig. 12 Chapter 5



Fig. 13 Confluence of Big Muddy River on left and Crab Orchard Creek on right showing water quality differences. (DVD 1 at 30:22)

Big and Little Muddy River-- Chapter 6




Fig. 14 Chapter 6

Recommendations—Little Muddy River—Chapters 7 -15

The recommended treatment for this segment is to treat the identified erosion sites and geotechnical failure sites with a series of Stream Barbs. The result of treatment will be the redirection of flow toward the center of the channel causing some re-aeration to occur. The stream barbs will also trap sediment near the failed banks and stop the bank erosion while adding significant sediment which can help prevent future geotechnical failures.

Table 3 will provide the estimated lengths and cost to apply stream barbs in this segment by chapter.

TREATMENT CHAPTER 7-15 : Little Muddy River Lateral Bank Treatment with Stream Barbs					
Chapter	Geotech or Erosion Sites	Average Length	Total Length	Average Cost/foot	Total Cost
7	26	400	10400	\$50.00	\$520,000
8	21	400	8400	\$50.00	\$420,000
9	21	400	8400	\$50.00	\$420,000
10	25	350	8750	\$50.00	\$437,500
11	34	350	11900	\$50.00	\$595,000
12	16	350	5600	\$50.00	\$280,000
13	26	300	7800	\$50.00	\$390,000
14	35	300	10500	\$50.00	\$525,000
15	11	300	3300	\$50.00	\$165,000
Total	215		75050		\$3,752,500

Table 3. Treatment needs for Chapters 7 -15

Big and Little Muddy River-- Chapter 7




Fig. 15 Chapter 7

Big and Little Muddy River-- Chapter 8




Fig. 16 Chapter 8

Big and Little Muddy River-- Chapter 9




Fig. 17 Chapter 9



Fig. 18 Low water crossing on DVD 2 at 14:48 acting as grade control and providing some re-aeration.



Fig. 19 Grade Control on DVD 2 at 11:20. Provides some re-aeration of flow.

Big and Little Muddy River-- Chapter 10




Fig. 20 Chapter 10

Big and Little Muddy River-- Chapter 11




Fig. 21 Chapter 11

Big and Little Muddy River-- Chapter 12




Fig. 22 Chapter 12

Big and Little Muddy River-- Chapter 13




Fig. 23 Chapter 13

Big and Little Muddy River-- Chapter 14




Fig. 24 Chapter 14



Fig. 25 Woody debris in channel from erosion on DVD tape 2 at 34:06

Big and Little Muddy River-- Chapter 15




Fig. 26 Chapter 15