



HURST-ROSCHÉ, INC.

TECHNICAL SPECIFICATIONS

**CIPP SEWER LINING
MAIN TRUNKLINE
LEVIN DRIVE TO JEROME LANE**

CITY OF CAHOKIA HEIGHTS

Project funded by

**ILLINOIS ENVIRONMENTAL
PROTECTION AGENCY GRANT**

Prepared by

**Hurst-Rosche, Inc.
5 Bank Square
East St. Louis, Illinois
H-R 860-0683**

August 2023

TABLE OF CONTENTS

Technical Specifications

| <u>DIVISION</u> | <u>SECTION</u> | <u>TITLE</u> | <u>PAGES</u> |
|-----------------|-----------------------------|---|--------------|
| 1 | <u>GENERAL REQUIREMENTS</u> | | |
| | 01031 | Additional Project Information | 01031-1 -4 |
| 2 | <u>SITE WORK</u> | | |
| | 02400 | Dewatering & Sewer Bypass | 02400-1 |
| | 02480 | Seeding | 02480-1 -2 |
| | 02731 | Sewer Cleaning, Main Sewers | 02731-1 -2 |
| | 02732 | Television Inspection, Main Sewers | 02732-1 -2 |
| | 02734 | Flow Control | 02734-1 |
| | 02735 | Cured-in-Place Pipe, Main Sewers (CIPP) | 02735-1 -5 |

INDEX OF STANDARDS

| | |
|-----------|--|
| 000001-08 | Standard Symbols, Abbreviations and Patterns |
| 701301-04 | Lane Closure, 2L, 2W, Short Time Operations |
| 701501-06 | Urban Lane Closure, 2L, 2W Undivided |
| 701901-08 | Traffic Control Devices |

End TOC

DIVISION 1 - GENERAL REQUIREMENTS
Section 01031 – Additional Project Information

1. GENERAL

1.1 SUMMARY

- A. Piezometers have been installed at the following locations to provide ground water information in the vicinity of the sanitary sewer trunkline rehabilitation locations:
 - 1. Piezometer PZ 7 - 2102 Florence Place (East End of Florence Place)
 - 2. Piezometer PZ 10 - 4222 Andrews Drive (at St. Christopher Lane)
 - 3. Piezometer MW-1285M - Levee Road (North of Levin Drive)

- B. Copies of the following additional project information is included in this section:
 - 1. Piezometer Readings

- C. The piezometer readings contained herein are presented for general information. The groundwater monitoring information has been conducted in accordance with standard practices and procedures. The results of these monitoring activities represent the subsurface conditions at the specific locations and dates indicated. Subsurface conditions between these locations and on differing dates may vary. The information provided herein is not intended as a substitute for the personal investigation, independent interpretation, and judgment of the contractor.

END 01031

PIEZOMETER READINGS
CITY OF CAHOKIA HEIGHTS

Piezometer PZ 7
2102 Florence Place
(East End of Florence Place)

| PIEZOMETER READINGS | | |
|------------------------|-------|-----------|
| (GROUND ELEVATION 418) | | |
| DATE | DEPTH | ELEVATION |
| 08/01/22 | 15 | 403 |
| 08/15/22 | 15 | 403 |
| 09/01/22 | 15 | 403 |
| 09/15/22 | 15 | 403 |
| 10/01/22 | 16 | 402 |
| 10/15/22 | 16 | 402 |
| 11/01/22 | 16 | 402 |
| 11/15/22 | 15 | 403 |
| 12/01/22 | 16 | 402 |
| 12/15/22 | 16 | 402 |
| 01/01/23 | 15 | 403 |
| 01/15/23 | 15 | 403 |
| 02/01/23 | 15 | 403 |
| 02/15/23 | 15 | 403 |
| 03/01/23 | 15 | 403 |
| 03/15/23 | 15 | 403 |
| 04/01/23 | 14 | 404 |
| 04/15/23 | 14 | 404 |
| 05/01/23 | 15 | 403 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| AVERAGE | 15 | 403 |

PIEZOMETER READINGS
CITY OF CAHOKIA HEIGHTS

Piezometer MW-1285M
Levee Road
(North of Levin Drive)

| PIEZOMETER READINGS | | |
|----------------------------|-----------|------------|
| (GROUND ELEVATION 402) | | |
| DATE | DEPTH | ELEVATION |
| 08/01/22 | 11 | 391 |
| 08/15/22 | 13 | 389 |
| 09/01/22 | 14 | 388 |
| 09/15/22 | 15 | 387 |
| 10/01/22 | 16 | 386 |
| 10/15/22 | 16 | 386 |
| 11/01/22 | 17 | 385 |
| 11/15/22 | 17 | 385 |
| 12/01/22 | 17 | 385 |
| 12/15/22 | 17 | 385 |
| 01/01/23 | 17 | 385 |
| 01/15/23 | 17 | 385 |
| 02/01/23 | 17 | 385 |
| 02/15/23 | 17 | 385 |
| 03/01/23 | 17 | 385 |
| 03/15/23 | 15 | 387 |
| 04/01/23 | 12 | 390 |
| 04/15/23 | 12 | 390 |
| 05/01/23 | 11 | 391 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| AVERAGE | 15 | 387 |

1. GENERAL

1.1 REQUIREMENTS INCLUDE

A. Contractor provide:

1. Dewatering of excavation to allow construction of sewers, manholes, and appurtenances in the dry and with firm excavation walls and foundation.
2. Bypass of flowing sewer mains around the excavation site to downstream manholes.

2. EXECUTION

2.1 DEWATERING:

- A. The Contractor shall install and operate a suitable dewatering system to allow all work related to the construction of the sewer mains to be accomplished in the dry and with firm excavation walls and foundation. Water which has accumulated in excavated areas shall be removed by the Contractor. The dewatering system shall be installed prior to beginning excavation activities and shall be of such type and operated in such a manner so as not to remove material from the foundation or wall area of the excavation. All dewatering and related equipment and materials shall be and remain the Contractor's property and, when no longer required, shall be removed in their entirety from the site. Any holes shall be backfilled with material similar to that of the adjacent area and compacted to the density of the material surrounding the hole. Dewatering facilities to be constructed under this Contract shall be included in the base bid.

2.2 SEWER BYPASS:

- A. Sewer flows shall be maintained at all times and shall be in accordance with local health and sanitary requirements. Bypass pumping shall be coordinated 48 hours in advance with the Owner's Representative. Pumping, temporary connections or other suitable methods of diversion shall be employed so that the flow of sewage shall not be interrupted.
- B. Sewage flows will be intercepted at existing manholes and bypass pumped. The Contractor will be required to furnish pumping equipment, conduits, and other equipment required to maintain flow without causing overflows backups, surges or any other abnormal flow conditions.
- C. When bypass pumps are in use, they shall be monitored by the Contractor at all times.
- D. Bypass pumping will be performed such that existing sewer lines are never placed under more than 3 feet of hydraulic head as measured from the sewer invert at the pump location.
- E. Individual service laterals encountered during construction shall be diverted to the nearest downstream manhole. The cost of such diversion will be considered incidental to the construction of the sewer and shall be included in the base bid.

END 02400.

1. GENERAL

1.1 REQUIREMENTS INCLUDE

A. Contractor:

1. Provide all materials, labor and equipment for seeding and mulching all disturbed areas of excavation and all other disturbed areas within the construction limits that will not be resurfaced.

1.2 REFERENCES. Specified references or cited portions thereof, current at date of bidding documents unless otherwise specified, govern the work. References to measurement and basis of payment made in any cited reference do not apply.

- A. Illinois Department of Transportation (IDOT): Standard Specifications for Road and Bridge Construction, including all addenda.

2. PRODUCTS

2.1 MATERIALS

- A. All seeding materials shall be in accordance with Sections 250, 251 and 1081 of the IDOT Standard Specifications.
- B. The seed mixture shall be Class 1 - Lawn Mixture in accordance with Article 250.07 of the IDOT Standard Specifications.

3. EXECUTION

3.1 SOIL PREPARATION

- A. After all trenches have been backfilled; the areas to be seeded shall be prepared in accordance with Article 250.05 of the IDOT Standard Specifications.

3.2 FERTILIZER

- A. Fertilizer nutrient shall be a 10-10-10 proportion applied at the rate of 270 pounds per acre. This is the weight of the nutrient only and does not include the weight of the filler material. The fertilizer shall conform to Article 1081.08 of the IDOT Standard Specifications.

3.3 SEEDING

- A. The rate of application shall be 100 pounds/acre in accordance with Article 250.07 IDOT Standard Specifications. The area shall be continuously reseeded until a sound turf is established.
- B. Seeding equipment and construction operations shall be in accordance with Section 250.03 of the IDOT Standard Specifications.

3.4 MULCHING

- A. All seeded areas shall be mulched. Mulching materials, equipment and construction operations shall be in accordance with Section 251 of the IDOT Standard Specifications. Mulch shall be applied uniformly to all seeded areas at the rate of two tons per acre by Method 1 as described in Article 251.03 of the IDOT Standard Specifications.

END 02480

DIVISION 2 - SITE WORK

Section 02731 - Sewer Cleaning, Main Sewers

1. GENERAL

1.1 REQUIREMENTS INCLUDE

A. Contractor provide:

1. All labor, equipment, materials, plant and supervision to perform all work necessary to clean existing sewers in accordance with these specifications and as shown on the plans.

1.2 DEFINITIONS

- A. The term "Clean" as used in these specifications, shall be defined as removing sufficient material to render the sewer line 99% of its original capacity.
- B. The term "Reach" as used in the specifications, shall mean the length of pipe connecting two manholes.

2. EXECUTION

2.1 GENERAL

A. Hydraulic Cleaning Equipment:

1. The equipment used shall be of a movable dam type and shall be constructed in such a way that a portion of the dam may be collapsed at any time during the cleaning operation to protect against flooding of the sewer. Sewer cleaning balls or other such equipment which cannot be collapsed instantly will not be considered as acceptable cleaning equipment. The movable dam shall be of equal diameter as the pipe being cleaned and shall provide a flexible scraper around the outer periphery to insure total removal of grease. Other equipment which produces the desired end results will be approved by the Owner's Representative.

B. High Velocity Hydro-Cleaning Equipment

1. All high-velocity sewer cleaning equipment shall be truck-mounted for ease of operation. The equipment shall have a minimum of 500 feet of 3/4" I.D. high-pressure hose with a selection of two or more high-velocity nozzles. The nozzles shall have a capacity of 30 GPM at a working pressure of 500 to 1,500 psi. The nozzle shall be capable of producing a scouring action from 15 degrees to 45 degrees in all size lines designated to be cleaned. Equipment shall also include a high velocity gun for washing and scouring manhole walls and floors. The gun capacity shall equal 3 1/2 to 27 GPM at between 800 and 2090 psi. The gun shall be capable of producing flows from a fine spray to a long distance solid stream. The equipment shall carry its own 1,200-gallon water tank capable of holding corrosive or caustic cleaning or sanitizing chemicals, auxiliary engines and pumps, and hydraulically driven hose

reel. All controls shall be located so that the equipment can be operated above ground. Other equipment which produces the desired end result will be approved by the Owner's Representative.

C. Water for Cleaning

1. Water will be available only at those locations designated by the City of Cahokia Heights. Water shall be conserved and not wasted. The Contractor will be responsible for acquiring water from the City of Cahokia Heights. The Contractor will not be charged for the use of said water.

D. Disposal of Material

1. All sludge, dirt, sand, rocks, grease and other solid or semi-solid material removed during the cleaning operation shall be removed at the downstream manhole of the reach being cleaned. Passing material from reach to reach, which could cause line stoppages, accumulations of sand in wetwells or damage to pumping equipment will not be permitted.
2. When hydraulic cleaning equipment is used, a suitable weir or dam shall be constructed in the downstream manhole in such a manner that both the solids and water shall be trapped. This trapped solution shall then be pumped, using a four-inch double diaphragm trash pump, from the manhole into a retention chamber above ground. The retention chamber shall be of a size of not less than 10 feet by 6 feet by 1 foot high and shall be mounted for complete mobility. The chamber shall contain not less than two baffles to ensure complete settlement of the solids before returning the liquid to the sewer line.
3. All solids or semi-solids resulting from the cleaning operations shall be removed from the site and disposed of by the Contractor, as approved by the Owner's Representative. Removal and disposal in compliance with all local health and sanitary requirements and to the approval of the Owner's Representative will be incidental to the cleaning of the sewer lines.

E. Final Acceptance of Cleaning

1. Any damage to sanitary sewers resulting from the cleaning operations shall be the responsibility of the Contractor, and necessary repairs shall be made by the Contractor at no additional expense to the Owner. Final acceptance of this portion of the work shall be made upon completion of the television inspection and shall be to the entire satisfaction of the Owner's Representative.

END 02731.

DIVISION 2 - SITE WORK
Section 02732 - Television Inspection,
Main Sewers

1. GENERAL

1.1 REQUIREMENTS INCLUDE:

A. Contractor provide:

1. Television inspection of sewers is to be conducted only after cleaning and sewer replacement have been accomplished.

2. EXECUTION

2.1 GENERAL

A. Television Inspection, Main Sewers:

1. The sewer sections shall be visually inspected by means of closed-circuit television. The inspection will be done one manhole section at a time and the flow in the section being inspected will be suitably controlled as specified.
2. The television camera used for the inspection shall be one specifically designed and constructed for such inspection. Lighting for the camera shall be suitable to allow a clear picture of the entire periphery of the pipe. The camera shall be operative in 100% humidity conditions. The camera, television monitor, videotape recorder, and other components of the video system shall be capable of producing picture quality to the satisfaction of the Owner's Representative; and if unsatisfactory, the equipment shall be removed, and no payment will be made for an unsatisfactory inspection.
3. The camera shall be moved through the line in either direction at a moderate rate, stopping when necessary to permit proper documentation of the sewer's condition. In no case will the television camera be pulled at a speed greater than 30 feet per minute. Manual winches, power winches, TV cable, and powered rewinds or other devices that do not obstruct the camera view or interfere with proper documentation of the sewer conditions shall be used to move the camera through the sewer line. If, during the inspection operation, the television camera will not pass through the entire manhole section, the Contractor shall set up his own equipment so that the inspection can be performed from the opposite manhole. If, again, the camera fails to pass through the entire manhole section, the inspection shall be considered complete and no additional inspection will be required.
4. When manually operated winches are used to pull the television camera through the line, telephones or other suitable means of communication shall be set up between the two manholes of the section being inspected to insure good communications between members of the crew.
5. The importance of accurate distance measurements is emphasized. Measurement for location of defects shall be above ground by means of a meter device. Marking on the cable, or the like, which would require interpolation for depth of manhole, will not be allowed. Accuracy of the

distance meter shall be checked by use of a walking meter, roll-a-tape, or other suitable device, and the accuracy shall be satisfactory to the Owner's Representative.

B. Documentation of the television results shall be as follows:

1. Television Inspection Logs: Printed location records shall be kept by the Contractor and will clearly show the location in relation to an adjacent manhole. In addition, other points of significance such as locations of building sewers and other discernible features will be recorded, and a copy of such records will be supplied to the Owner.
2. Digital Format Video Recordings: The purpose of the video recordings shall be to supply a visual and audio record of problem areas of the lines that may be replayed. The video shall be a CD or DVD with a high quality picture and sound and shall be recorded in color. The video shall have an on-screen display showing the following:
 - a. Upstream and downstream manhole numbers.
 - b. Footage from the upstream manhole.
 - c. Date of inspection.
3. Two copies of the inspection logs and video recordings of all inspections shall be furnished to the Owner.

END 02732.

DIVISION 2 - SITE WORK
Section 02734 - Flow Control

1. GENERAL

1.1 REQUIREMENTS INCLUDE:

A. Contractor provide:

1. Sewer flows through the reaches to be televised, as well as through all tributary sewers, shall be maintained at all times throughout the entire project.
2. A fully operational back-up pump shall be maintained on site at all times for emergencies during care of flow/by-passing operations. The capacity of the back-up pump shall be sufficient to maintain sewer flows.

2. EXECUTION

2.1 CARE OF FLOW

A. General:

1. Sewer flows shall be maintained at all times and shall be in accordance with local health and sanitary requirements by pumping, fluming, temporary connections or by other suitable methods of diversion so that the project will not be delayed nor the flow of sewage interrupted.
2. When sewer line flows are above minimum requirements (generally not more than 1/4 of the pipe diameter) or inspection of the complete periphery of the pipe is necessary to effectively conduct the inspection and sealing operations, one or more of the following methods of flow control shall be used.
3. In order to accomplish the cleaning and television inspection in this contract, normal sewage flows must be maintained. Sewage flows shall be intercepted at existing manholes and restricted or bypass pumped as directed by the Owner's Representative. Where pumping is required, in the opinion of the Owner's Representative, to assure completion of the inspection and lining work, the Contractor will be required to furnish pumping equipment, conduits and other equipment necessary to bypass the sewage flows.
4. The bypass system shall be such that the maximum hydraulic head on the existing sewer line, when measured by the location of the pump, is less than 3.0 feet at all times. The hydraulic head shall be measured from the invert of the sewer.
5. Pumping will not be permitted unless other methods of sewer flow controls prove unsatisfactory for television observation. Bypass pumping for television inspection shall be included in the contract price for the work. Methods of controlling flow other than pumping shall be incidental to the cleaning and televising.

END 02734

1. GENERAL

1.1 REQUIREMENTS INCLUDE

A. Contractor provide:

1. Intent: It is the intent of this specification to provide for the rehabilitation of sanitary sewers by the installation of a resin-impregnated flexible felt tube inserted into the existing pipe using hydrostatic pressure or other means. Curing shall be accomplished by circulating hot water, or other approved method, to cure the resin to a hard, impermeable, corrosion resistant pipe within a pipe.
2. This specification references ASTM standards, which are made a part hereof by reference and shall be the latest edition thereof.
3. Chemical Resistance Requirements: The finished pipe in place shall be fabricated from materials which when cured will meet the chemical resistance guidelines of ASTM F-1216.

1.2 PRODUCT DELIVERY, STORAGE AND HANDLING

- A. Transport, deliver, unload, store, and handle all felt tube and fittings in a manner to prevent damage to the materials or the work.
- B. All damaged, broken or otherwise defective materials will be rejected.

1.3 MEASUREMENT AND PAYMENT

- A. Payment for the work included in this section will be in accordance with the prices set forth in the proposal for the quantity of work performed. Progress payments will be made monthly based on the work performed during that period.
- B. Measurement for lineal feet (LF) of CIPP installed shall be from center of manhole to center of manhole for complete, entire reaches of sewer. For partial reaches, measurement shall be from starting manhole center to end of installed length, as determined by length of liner pipe used.

2. PRODUCTS

2.1 GENERAL SPECIFICATIONS GOVERNING THE WORK

- A. The materials provided under this section shall conform to ASTM F1216 and the requirements of the CIPP manufacturer.
- B. Installation of CIPP by the "pull-in and inflate" method in accordance with ASTM F1743 is an acceptable alternative to ASTM F1216 for this project.
- C. The Contractor shall field verify the diameter and length of the existing pipeline prior to ordering the liner material.

2.2 PRODUCT, MANUFACTURER/INSTALLER QALIFICATION REQUIREMENTS

- A. Since sewer products are intended to have a 50-year design life, and in order to minimize the Owner's risk, only proven products with substantial successful long-term track records will be approved. All trenchless rehabilitation products and installers must be pre-approved prior to the formal opening of proposals.
- B. Products and Installers seeking approval must meet all of the following criteria to be Commercially Acceptable:
 - 1. For a Product to be considered Commercially Proven, a minimum of five successful wastewater collection system projects of a similar size and scope of work shall be performed in the U.S. and documented to the satisfaction of the Owner to assure commercial viability.
 - 2. For an Installer to be considered as Commercially Proven, the installer must satisfy all insurance, financial, and bonding requirements of the Owner, and must have had at least 5 (five) years active experience in the commercial installation. In addition, the Installer must have successfully installed at least 1,000,000 feet of a cured-in-place product in wastewater collection systems. Acceptable documentation of these minimum installations must be submitted to the Owner. Installer's project managers must have a minimum of 2 years of CIPP installation experience and must be on-site during the installation of the CIPP products.
 - 3. Sewer rehabilitation products submitted for approval must provide third party test results supporting the structural performance (short-term and long-term) of the product and such data shall be satisfactory to the Owner. No product will be approved without independent third party testing verification.
 - 4. The rehabilitation manufacturing process shall operate under a quality management system which is third-party certified to ISO 9000 or other recognized organization standards. Proof of certification shall be required for approval.
 - 5. The owner authorizes the use of proven materials that serve to enhance the pipe performance specified herein. Proven materials have passed independent laboratory testing, not excluding long-term (10,000 hour) structural behavior testing, and have been successfully installed to repair failing host pipes in the U. S. for at least 4 years. In addition to the aforementioned, the owner may require that the contractor demonstrate that the enhancements proposed exceed the specifications herein, prior to the installation of the enhanced material systems. This section in no way shall be interpreted as authorization to deviate from the minimum standard practices set forth herein.

2.3 MATERIALS

- A. Tube - the sewn tube shall meet the requirements of ASTM F1216, Section 5.1 and shall not contain fiberglass continuous strand matt. The tube shall be constructed to withstand installation pressures, have sufficient strength to bridge missing pipe, stretch to fit irregular pipe sections, and shall install smoothly around bends.
 - 1. The wetout tubes shall have a uniform thickness that when compressed

- at installation pressures will meet or exceed the design thickness.
2. The tube shall be made to a size that when installed will tightly fit the internal circumference and length of the original pipe. Allowance should be made for circumferential stretching during installation.
 3. The outside layer of the tube (before wetout) shall be polyethylene coated, a translucent flexible material that clearly allows inspection of the resin impregnation (wetout) procedure. The plastic coating shall hold the resin inside the tube without leakage, accommodate installation, stretch to size and shall not delaminate before, during or after curing of the CIPP.
 4. The tube shall be homogeneous across the entire wall thickness containing no intermediate or encapsulated elastomeric layers. No material shall be included in the tube that may cause delamination in the cured CIPP. No dry or unsaturated layers shall be evident.
 5. The wall color of the interior pipe surface of the CIPP after installation shall be a light reflective color so that a clear detail examination with closed circuit television inspection equipment may be made.
 6. Seams in the tube shall be stronger than the unseamed felt. Where the length requires joining, the sewn joint shall not be perpendicular to the long axis but spirally formed and sewn.

B. Resin - The resin system shall be a corrosion resistant polyester, vinyl ester, or epoxy and catalyst system that meets the requirements of ASTM F1216, and the physical properties stipulated herein.

C. Structural Requirements

1. The CIPP shall be designed as per ASTM F1216, Appendix X1. The CIPP design shall assume no bonding to the original pipe wall. The Long-Term Flexural Modulus shall be substantiated by independent lab testing (such as the Trenchless Technology Center at Louisiana Tech University). Such Long-Term Modulus shall not exceed 50% of the short-term values specified herein.
2. The layers of the cured CIPP shall be uniformly bonded. It shall not be possible to separate any two layers with a probe or point of a knife blade so that the layers separate cleanly, or the probe or knife blade moves freely between the layers. If separation of the layers occurs during testing of field samples, new samples will be cut from the work. Any reoccurrence may cause rejection of the work.
3. The cured pipe material (CIPP) shall conform to the structural properties, as listed below (if the contractor uses a modulus of elasticity other than 400,000 psi, then design calculations for the proposed system must be submitted for review and approval prior to installation):

| | | |
|-------------------|-----------|-------------|
| Modulus of | | |
| Elasticity | ASTM D790 | 400,000 psi |
| Flexural Strength | ASTM D790 | 4,500 psi |

4. The required structural CIPP wall thickness shall be based on the following design parameters.
 - a. Fully deteriorated pipe.
 - b. Design safety factor of 2.0.
 - c. Ovality of 5%.

- d. Ground water depth = 5 feet above crown of sewer.
 - e. Soil depth (above crown of pipe) = 22 feet.
 - f. Soil modulus = 700 psi.
 - g. Soil density = 120 lb./cu.ft.
 - h. Live load = H20 Highway, 16,000 lbs.
5. The Contractor must have performed long-term testing for flexural creep of the CIPP pipe material installed by his Company. Such testing results are to be used to determine the long-term, time dependent flexural modulus to be utilized in the product design. This is a performance test of the materials (Tube and Resin) and general workmanship of the installation and curing as defined within the relevant ASTM standard. A percentage of the instantaneous flexural modulus value (as measured by ASTM D790 testing) will be used in design calculations for external buckling. The percentage, or the long-term creep retention value utilized, will be verified by this testing. Retention values exceeding 50% of the short-term test results shall not be applied unless substantiated by qualified third party test data to the Owner's satisfaction. The materials utilized for the contracted project shall be of a quality equal to or better than the materials used in the long-term test with respect to the initial flexural modulus used in the CIPP design.
6. The Enhancement Factor 'K' to be used in 'Partially Deteriorated' Design conditions shall be assigned a value of 7.

D. Testing Requirements

- 1. Chemical Resistance - The CIPP shall meet the chemical resistance requirements of ASTM F1216, Appendix XII. CIPP samples for testing shall be of tube and resin system similar to that proposed for actual construction. It is required that CIPP samples with and without plastic coating meet these chemical-testing requirements.
- 2. Hydraulic Capacity - Overall, the Hydraulic profile shall be maintained as large as possible. The CIPP shall, as a minimum, have the full flow capacity of the original pipe before rehabilitation. Calculated capacities may be derived using a commonly accepted roughness coefficient for the existing pipe material taking into consideration its age and condition. The roughness coefficient of the CIPP shall be verified by third party test data.
- 3. CIPP Field Samples - When requested by the Owner's Representative, the Contractor shall submit test results from previous field installation in the USA of the same resin system and tube materials as proposed for the actual installation. These test results must verify that the CIPP physical properties specified have been achieved in previous field applications. Testing samples for this project shall be made and tested as specified herein.

3. EXECUTION

3.1 COORDINATION

- A. The Contractor shall schedule work and notify all contractors in ample time so that provisions for their work can be made without delaying the progress of the project.

- B. The Contractor shall make every effort to maintain service usage throughout the duration of the project. In the event that a service will be temporarily out of service, the maximum amount of time of no service shall be 12 hours for any property served by the sewer. The Contractor shall be required to notify the Owner and all affected properties whose service laterals will be out of commission and to advise against water usage until the sewer main is back in service. Such notification shall be provided to the Utility Department at least one week prior to service disconnecting.
- C. Public Notification - A public notification program shall be implemented, and shall as a minimum, require the Contractor to be responsible for contacting each home or business connected to the sanitary sewer and inform them of the work to be conducted, and when the sewer will be off-line. The Contractor shall also provide the following:
 - a. Written notice to be delivered to each home or business describing the work, schedule, how it affects them, and a local telephone number of the Contractor they can call to discuss the project or any problems which could arise.
 - b. Personal contact and attempted written notice the day prior to the beginning of work being conducted on the section relative to the residents affected.
 - c. Personal contact with any home or business that cannot be reconnected within the time stated in the written notice.
- D. Preparatory Procedures: The following procedures shall be adhered to unless otherwise approved by the Owner's Representative.
 - 1. Cleaning: It shall be the responsibility of the Contractor to clean the pipeline with a high-pressure water jet of 1,500 to 2,000 psi maximum capacity and to remove internal debris out of the pipeline.
 - 2. TV Inspection: Inspection shall be performed by experienced personnel. The interior of the pipeline shall be carefully inspected using closed-circuit television or other means to determine conditions, which may prevent proper installation, and it shall be noted so that these conditions can be corrected.
 - 3. Obstruction Removal: The Contractor shall remove obstructions and intruding service connections that may prevent proper installation.
 - 4. Flow Control: The Contractor shall provide for the bypassing of sewage entering or passing through the pipe to be rehabilitated.
 - 5. Line Obstructions: It shall be the responsibility of the Contractor to clear the line of obstructions such as solids and roots that will prevent the installation of CIPP. If pre-installation inspection reveals an obstruction such as a protruding service connection, dropped joint, or a collapse that will prevent the installation process, and it cannot be removed by conventional sewer cleaning equipment, then the contractor shall make a point repair excavation to uncover and remove or repair the obstruction. Such excavation shall be approved in writing by the Owner's representative prior to the commencement of the work and shall be considered as a separate pay item.

3.2 INSTALLATION

- A. General:

1. The Contractor shall be responsible for confirming the locations of all branch service connections prior to installation and curing the CIPP.
2. The Contractor shall designate a location where the tube will be impregnated with resin using vacuum and distribution rollers to thoroughly saturate the tube prior to installation. The Contractor shall allow the Owner to inspect the materials and the "wet-out" procedure.
3. Resin Impregnation - The quantity of resin used for tube impregnation shall be sufficient to fill the volume of air voids in the tube with additional allowances for polymerization shrinkage and the loss of resin through cracks and irregularities in the original pipe wall. A roller system shall be used to uniformly distribute the resin throughout the tube.
4. After the installation is complete, the Contractor shall supply a suitable heat source and water recirculation equipment. The equipment shall be capable of uniformly raising the water temperature to a level required to effectively cure the resin.
5. The heat source shall be fitted with suitable monitors to gauge the temperature of the incoming and outgoing water supply. Another such gage shall be placed inside the tube at the downstream manhole at or near the bottom to determine the temperatures during cure. Water temperature in the pipe during the cure period shall be as recommended by the resin manufacturer.
6. Initial cure shall be deemed complete when inspection of the exposed portions of the tube appear to be hard and sound and the temperature sensor indicates that the temperature is of a magnitude to realize an exotherm. The cure period shall be of a duration recommended by the resin manufacturer and may require continuous recirculation of the water to maintain the temperature.
7. Cooldown: The Contractor shall cool the hardened pipe to a temperature below 100°F before relieving the hydrostatic head. Cool down may be accomplished by the introduction of cool water into the pipe to replace water being pumped out of the manhole.
8. Finish: The new pipe shall be cut off in the manhole at a suitable location. The finished product shall be continuous over the length of pipe reconstructed and be free from dry spots, delamination and lifts. It shall also meet the leakage requirements or pressure test specified below. During the warranty period, any defects which will affect the integrity or strength of the product, shall be repaired at the Contractor's expense, in a manner mutually agreed upon by the Owner and the Contractor.
9. After the pipe has been cured in place, the Contractor shall reconnect the existing service connections. This shall be done from the interior of the pipeline without excavation using a robotic cutter. The Contractor shall certify he has a minimum of 2 complete working cutter units plus spare key components on the site before each installation. No additional payment will be made for excavations for the purpose of reopening connections and the Contractor will be responsible for all costs and liability associated with such excavation and restoration work.

B. Testing

1. The water tightness of the cured-in-place pipe shall be gauged while curing and under a positive head.
2. For each installed length designated by the Owner in the contract

documents or purchase order, one CIPP sample shall be prepared from a section of the cured pipe at an intermediate manhole or at the termination point that has been installed through a like diameter pipe held in place by a suitable heat sink, such as sandbags. In areas with limited space and large diameter pipes, other sampling techniques may be required. The CIPP samples shall be tested in accordance with ASTM D-790 except that the full sample thickness shall be tested. The flexural properties of the samples shall meet the requirements specified in this section.




3. Visual inspection of the CIPP shall be in accordance with ASTM F1216, Section 8.4.

C. Cleanup

1. Upon acceptance of the installation work and testing, the Contractor shall reinstate the project area affected by his operations.

END 02735

| | | | | | | | | | |
|-----------------|-------------------------------|--------|---------------------------------------|--------|-----------------------------|-----------------|---|-----------|--------------------------------|
| ABV | ABOVE | CU YD | CUBIC YARD | HATCH | HATCHING | PM | PAVEMENT MARKING | STD | STANDARD |
| A/C | ACCESS CONTROL | CULV | CULVERT | HD | HEAD | PED | PEDESTAL | SBI | STATE BOND ISSUE |
| AC | ACRE | C&G | CURB & GUTTER | HDW | HEADWALL | PNT | POINT | SR | STATE ROUTE |
| ADJ | ADJUST | D | DEGREE OF CURVE | HDUTY | HEAVY DUTY | PC | POINT OF CURVATURE | STA | STATION |
| AS | AERIAL SURVEYS | DC | DEPRESSED CURVE | ha | HECTARE | PI | POINT OF INTERSECTION OF HORIZONTAL CURVE | SPBGR | STEEL PLATE BEAM GUARDRAIL |
| AGG | AGGREGATE | DET | DETECTOR | HMA | HOT MIX ASPHALT | PRC | POINT OF REVERSE CURVE | SS | STORM SEWER |
| AH | AHEAD | DIA | DIAMETER | HWY | HIGHWAY | PT | POINT OF TANGENCY | STY | STORY |
| APT | APARTMENT | DIST | DISTRICT | HORIZ | HORIZONTAL | POT | POINT ON TANGENT | ST | STREET |
| ASPH | ASPHALT | DOM | DOMESTIC | HSE | HOUSE | POLYETH | POLYETHYLENE | STR | STRUCTURE |
| AUX | AUXILIARY | DBL | DOUBLE | IL | ILLINOIS | PCC | PORTLAND CEMENT CONCRETE | e | SUPERELEVATION RATE |
| AGS | AUXILIARY GAS VALVE (SERVICE) | DSEL | DOWNSTREAM ELEVATION | IMP | IMPROVEMENT | PP | POWER POLE OR PRINCIPAL POINT | S.E. RUN. | SUPERELEVATION RUNOFF LENGTH |
| AVE | AVENUE | DSFL | DOWNSTREAM FLOWLINE | IN DIA | INCH DIAMETER | PRM | PRIME | SURF | SURFACE |
| AX | AXIS OF ROTATION | DR | DRAINAGE OR DRIVE | INL | INLET | PE | PRIVATE ENTRANCE | SMK | SURVEY MARKER |
| BK | BACK | DI | DRAINAGE INLET OR DROP INLET | INST | INSTALLATION | PE | PROFILE | T | TANGENT DISTANCE |
| B-B | BACK TO BACK | DRV | DRIVEWAY | IDS | INTERSECTION DESIGN STUDY | PROF | PROFILE | T.R. | TANGENT RUNOUT DISTANCE |
| BKPL | BACKPLATE | DCT | DUCT | INV | INVERT | PGL | PROFILE GRADELINE | TEL | TELEPHONE |
| B | BARN | EA | EACH | IP | IRON PIPE | PROJ | PROJECT | TB | TELEPHONE BOX |
| BARR | BARRICADE | EB | EASTBOUND | IR | IRON ROD | P.C. | PROPERTY CORNER | TP | TELEPHONE POLE |
| BL | BASELINE | EOP | EDGE OF PAVEMENT | JT | JOINT | PL | PROPERTY LINE | TEMP | TEMPORARY |
| BGN | BEGIN | E-CL | EDGE TO CENTERLINE | kg | KILOGRAM | PR | PROPOSED | TBM | TEMPORARY BENCH MARK |
| BM | BENCHMARK | E-E | EDGE TO EDGE | km | KILOMETER | R | RADIUS or RESIDENTIAL | TD | TILE DRAIN |
| BIND | BINDER | ELEC | ELECTRICAL | LS | LANDSCAPING | RR | RAILROAD | TBE | TO BE EXTENDED |
| BIT | BITUMINOUS | EL | ELEVATION | LN | LANE | RRS | RAILROAD SPIKE | TBR | TO BE REMOVED |
| BTM | BOTTOM | ENTR | ENTRANCE | LT | LEFT | RPS | REFERENCE POINT STAKE | TBS | TO BE SAVED |
| BLVD | BOULEVARD | EXC | EXCAVATION | LIDAR | LIGHT DETECTION AND RANGING | REF | REFLECTIVE | TWP | TOWNSHIP |
| BRK | BRICK | EX | EXISTING | LP | LIGHT POLE | RCCP | REINFORCED CONCRETE CULVERT PIPE | TR | TOWNSHIP ROAD |
| BBOX | BUFFALO BOX | EXPWAY | EXPRESSWAY | LGT | LIGHTING | REINF | REINFORCEMENT | TS | TRAFFIC SIGNAL |
| BLDG | BUILDING | E | EXTERNAL DISTANCE OF HORIZONTAL CURVE | LF | LINEAL FEET OR LINEAR FEET | REM | REMOVAL | TSCB | TRAFFIC SIGNAL CONTROL BOX |
| CATV | CABLE | E | OFFSET DISTANCE TO VERTICAL CURVE | L | LITER OR CURVE LENGTH | RC | REMOVE CROWN | TSC | TRAFFIC SYSTEMS CENTER |
| CIP | CAST IRON PIPE | F-F | FACE TO FACE | LC | LONG CHORD | REP | REPLACEMENT | TRVS | TRANSVERSE |
| CB | CATCH BASIN | FA | FEDERAL AID | LNG | LONGITUDINAL | REST | RESTAURANT | TRVL | TRAVEL |
| C-C | CENTER TO CENTER | FAI | FEDERAL AID INTERSTATE | L SUM | LUMP SUM | RESURF | RESURFACING | TRN | TURN |
| CL | CENTERLINE OR CLEARANCE | FAP | FEDERAL AID PRIMARY | MACH | MACHINE | RET | RETAINING | TY | TYPE |
| CL-E | CENTERLINE TO EDGE | FAS | FEDERAL AID SECONDARY | MB | MAIL BOX | RT | RIGHT | T-A | TYPE A |
| CL-F | CENTERLINE TO FACE | FAUS | FEDERAL AID URBAN SECONDARY | MH | MANHOLE | ROW | RIGHT-OF-WAY | TYP | TYPICAL |
| CTS | CENTERS | FP | FENCE POST | MATL | MATERIAL | RD | ROAD | UNDGND | UNDERGROUND |
| CERT | CERTIFIED | OPT | FIBER OPTIC | MED | MEDIAN | RDWY | ROADWAY | USGS | U.S. GEOLOGICAL SURVEY |
| CHSLD | CHISELED | FE | FIELD ENTRANCE | m | METER | RTE | ROUTE | USEL | UPSTREAM ELEVATION |
| CS | CITY STREET | FH | FIRE HYDRANT | METH | METHOD | SAN | SANITARY | USFL | UPSTREAM FLOWLINE |
| CP | CLAY PIPE | FL | FLOW LINE | M | MID-ORDINATE | SANS | SANITARY SEWER | UTIL | UTILITY |
| CLSD | CLOSED | FB | FOOT BRIDGE | mm | MILLIMETER | SEC | SECTION | VBOX | VALVE BOX |
| CLID | CLOSED LID | FDN | FOUNDATION | mm DIA | MILLIMETER DIAMETER | SEED | SEEDING | VV | VALVE VAULT |
| CT | COAT OR COURT | FR | FRAME | MIX | MIXTURE | SHAP | SHAPING | VL | VAULT |
| COMB | COMBINATION | F&G | FRAME & GRATE | MBH | MOBILE HOME | S | SHED | VEH | VEHICLE |
| C | COMMERCIAL BUILDING | FRWAY | FREEWAY | MOD | MODIFIED | SH | SHEET | VP | VENT PIPE |
| CE | COMMERCIAL ENTRANCE | GAL | GALLON | MFT | MOTOR FUEL TAX | SHLD | SHOULDER | VERT | VERTICAL |
| CONC | CONCRETE | GALV | GALVANIZED | N & BC | NAIL & BOTTLE CAP | SW | SIDEWALK OR SOUTHWEST | VC | VERTICAL CURVE |
| CONST | CONSTRUCT | G | GARAGE | N & C | NAIL & CAP | SIG | SIGNAL | VPC | VERTICAL POINT OF CURVATURE |
| CONTD | CONTINUED | GM | GAS METER | N & W | NAIL & WASHER | SOD | SODDING | VPI | VERTICAL POINT OF INTERSECTION |
| CONT | CONTINUOUS | GV | GAS VALVE | NC | NORMAL CROWN | SM | SOLID MEDIUM | VPT | VERTICAL POINT OF TANGENCY |
| COR | CORNER | GIS | GEOGRAPHICAL INFORMATION SYSTEM | NB | NORTHBOUND | SB | SOUTHBOUND | WM | WATER METER |
| CORR | CORRUGATED | GRAN | GRANULAR | NE | NORTHEAST | SE | SOUTHEAST | VV | WATER VALVE |
| CMP | CORRUGATED METAL PIPE | GR | GRATE | NW | NORTHWEST | SPL | SPECIAL | WMAIN | WATER MAIN |
| CNTY | COUNTY | GRVL | GRAVEL | O/S | OFFSET | SD | SPECIAL DITCH | WB | WESTBOUND |
| CH | COUNTY HIGHWAY | GND | GROUND | O&C | OIL AND CHIP | SQ FT | SQUARE FEET | WILDFL | WILDFLOWERS |
| CSE | COURSE | GUT | GUTTER | OLID | OPEN LID | m ² | SQUARE METER | W | WITH |
| XSECT | CROSS SECTION | GP | GUY POLE | PAT | PATTERN | mm ² | SQUARE MILLIMETER | WO | WITHOUT |
| m ³ | CUBIC METER | GW | GUY WIRE | PVD | PAVED | SQ YD | SQUARE YARD | | |
| mm ³ | CUBIC MILLIMETER | HH | HANDHOLE | PVMT | PAVEMENT | STB | STABILIZED | | |

| | |
|--|---------------|
|  Illinois Department of Transportation | |
| PASSED <u>January 1, 2021</u>  ENGINEER OF POLICY AND PROCEDURES | ISSUED 1-1-97 |
| APPROVED <u>January 1, 2021</u>  ENGINEER OF DESIGN AND ENVIRONMENT | |

| DATE | REVISIONS |
|--------|---|
| 1-1-21 | Updated fonts, abbreviations and symbols. |
| 1-1-19 | Added new symbols. |

STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

(Sheet 1 of 9)

STANDARD 000001-08

| <u>ADJUSTMENT ITEMS</u> | | <u>EX</u> | <u>PR</u> | <u>ALIGNMENT ITEMS</u> | | <u>EX</u> | <u>PR</u> | <u>DRAINAGE ITEMS</u> | | <u>EX</u> | <u>PR</u> |
|---------------------------------------|--|-----------|-----------|--------------------------------------|--|--|-----------|---------------------------|-------|-----------|-----------|
| Structure To Be Adjusted | | | ADJ | Baseline | _____ | _____ | | Channel or Stream Line | ----- | ----- | |
| Structure To Be Cleaned | | | C | Centerline | ----- | ----- | | Culvert Line | ----- | ----- | |
| Main Structure To Be Filled | | | FM | Centerline Break Circle | ○ | ⊙ | | Grading & Shaping Ditches | ----- | ----- | |
| Structure To Be Filled | | | F | Baseline Symbol | ⊥ | ⊥ | | Drainage Boundary Line | //// | //// | |
| Structure To Be Filled Special | | | FSP | Centerline Symbol | | ⊥ | | Paved Ditch | ----- | ----- | |
| Structure To Be Removed | | | R | PI Indicator | △ | △ | | Aggregate Ditch | ----- | ----- | |
| Structure To Be Reconstructed | | | REC | Point Indicator | ○ | ○ | | Pipe Underdrain | ----- | ----- | |
| Structure To Be Reconstructed Special | | | RSP | Horizontal Curve Data (Half Size) | EX. CURVE P.I. STA= Δ= D= R= T= L= E= e= T.R.= S.E. RUN= P.C. STA= P.T. STA= | CURVE P.I. STA= Δ= D= R= T= L= E= e= T.R.= S.E. RUN= P.C. STA= P.T. STA= | | Storm Sewer | ----- | ----- | |
| Frame and Grate To Be Adjusted | | | A | <u>BOUNDARIES ITEMS</u> | | <u>EX</u> | <u>PR</u> | Flowline | ⊥ | ⊥ | |
| Frame and Lid To Be Adjusted | | | A | Dashed Property Line | ----- | ----- | | Ditch Check | ◆ | ◆ | |
| Domestic Service Box To Be Adjusted | | | A | Solid Property/Lot Line | _____ | _____ | | Headwall | - | ∩ | |
| Valve Vault To Be Adjusted | | | A | Section/Grant Line | ----- | ----- | | Inlet | □ | ■ | |
| Special Adjustment | | | SP | Quarter Section Line | ----- | ----- | | Manhole | ⊙ | ⊙ | |
| Item To Be Abandoned | | | AB | Quarter/Quarter Section Line | ----- | ----- | | Summit | ↔ | ↔ | |
| Item To Be Moved | | | M | County/Township Line | ----- | ----- | | Roadway Ditch Flow | ~→ | ~→ | |
| Item To Be Relocated | | | REL | State Line | ----- | ----- | | Swale | → | → | |
| Pavement Removal and Replacement | | | | Chiseled Square Found | □ | □ | | Catch Basin | ○ | ● | |
| | | | | Iron Pipe Found | ○ | ● | | Culvert End Section | ◁ | ◁ | |
| | | | | Iron Pipe Set | ● | ● | | Water Surface Indicator | ▽ | ▽ | |
| | | | | Survey Marker | ⊙ | ⊙ | | Riprap | ▒ | ▒ | |
| | | | | Property Line Symbol | ⊥ | ⊥ | | <u>HYDRAULICS ITEMS</u> | | <u>EX</u> | <u>PR</u> |
| | | | | Same Ownership Symbol (Half Size) | ↗ | ↗ | | Overflow | ↪ | ↪ | |
| | | | | Northwest Quarter Corner (Half Size) | ⊙ | ⊙ | | Sheet Flow | → | → | |
| | | | | Section Corner (Half Size) | ⊙ | ⊙ | | Hydrant Outlet | → | → | |
| | | | | Southeast Quarter Corner (Half Size) | ⊙ | ⊙ | | | | | |

**STANDARD SYMBOLS,
ABBREVIATIONS
AND PATTERNS**
(Sheet 2 of 9)

STANDARD 000001-08

Illinois Department of Transportation

PASSED January 1, 2021

 ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021

 ENGINEER OF DESIGN AND ENVIRONMENT


ISSUED 1-1-97

EROSION & SEDIMENT CONTROL ITEMS

EX

PR

- Cleaning & Grading Limits
- Dike
- Erosion Control Fence
- Perimeter Erosion Barrier
- Temporary Fence
- Ditch Check Temporary
- Ditch Check Permanent
- Inlet & Pipe Protection
- Sediment Basin
- Erosion Control Blanket
- Fabric Formed Concrete Revetment Mat
- Turf Reinforcement Mat
- Mulch Temporary
- Mulch Method 1
- Mulch Method 2 Stabilized
- Mulch Method 3 Hydraulic




CONTOUR ITEMS

EX

PR

- Approx. Index Line
- Approx. Intermediate Line
- Index Contour
- Intermediate Contour




NON-HIGHWAY IMPROVEMENT ITEMS

EX

PR

- Noise Attn./Levee
- Field Line
- Fence
- Base of Levee
- Mailbox
- Multiple Mailboxes
- Pay Telephone
- Advertising Sign
- ITS* Camera
- Wind Turbine
- Cellular Tower




*Intelligent Transportation Systems

LANDSCAPING ITEMS

EX

PR

- Contour Mounding Line
- Fence
- Fence Post
- Shrubs
- Mowline
- Perennial Plants
- Seeding Class 2
- Seeding Class 2A
- Seeding Class 4
- Seeding Class 4 & 5 Combined




EXISTING LANDSCAPING ITEMS (contd.)

EX

PR

- Seeding Class 5
- Seeding Class 7
- Seedlings Type 1
- Seedlings Type 2
- Sodding
- Mowstake w/Sign
- Tree Trunk Protection
- Evergreen Tree
- Shade Tree




LIGHTING

EX

PR

- Duct
- Conduit
- Electrical Aerial Cable
- Electrical Buried Cable
- Controller
- Underpass Luminaire
- Power Pole



Illinois Department of Transportation

PASSED January 1, 2021
Michael Bond
 ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021
Joe E. Cole
 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
 (Sheet 3 of 9)

STANDARD 000001-08

**LIGHTING
(contd.)**

EX

PR

Pull Point



Handhole



Heavy Duty Handhole



Junction Box



Light Unit Comb.



Electrical Ground



Traffic Flow Arrow



High Mast Pole
(Half Size)



Light Unit-1




PAVEMENT (MISC.)


EX

PR


Keyed Long. Joint



Keyed Long. Joint w/Tie Bars



Sawed Long. Joint w/Tie Bars




Bituminous Shoulder



Bituminous Taper



Stabilized Driveway



Widening



PAVEMENT MARKINGS



EX

PR

Handicap Symbol



RR Crossing



Raised Marker Amber 1 Way





Raised Marker Amber 2 Way





Raised Marker Crystal 1 Way



Two Way Turn Left



Shoulder Diag. Pattern



Skip-Dash White




Skip-Dash Yellow




Stop Line





Solid Line



Double Centerline



Dotted Lines



Illinois Department of Transportation

PASSED January 1, 2021

 ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021

 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

**STANDARD SYMBOLS,
ABBREVIATIONS
AND PATTERNS**

(Sheet 4 of 9)

STANDARD 000001-08

PAVEMENT MARKINGS
(contd.)

CL 2Ln 2Way
RRPM 12.2 m (40') o.c.

CL 2Ln 2Way
RRPM 80' (24.4 m) o.c.

CL Multilane Div.
RRPM 40' (12.2 m) o.c.

CL Multilane Div.
RRPM 80' (24.4 m) o.c.

CL Multilane Div. Dbl.
RRPM 80' (24.4 m) o.c.

CL Multilane Undiv.

Two Way Turn Left Line

Urban Combination Left

Urban Combination Right

Urban Left Turn Arrow

Urban Right Turn Arrow


Urban Left Turn Only

Urban Right Turn Only

Urban Thru Only

EX

PR



ONLY
ONLY
ONLY



RAILROAD ITEMS



EX

PR

Abandoned Railroad



Railroad



Railroad Point



Control Box



Crossing Gate



Flashing Signal



Railroad Cant. Mast Arm



Crossbuck




REMOVAL ITEMS


EX

PR

Removal Tic



Bituminous Removal



Hatch Pattern



Tree Removal Single



RIGHT OF WAY ITEMS

EX

PR


Future ROW Corner Monument





ROW Marker




ROW Line



Easement



Temporary Easement



**STANDARD SYMBOLS,
ABBREVIATIONS
AND PATTERNS**

(Sheet 5 of 9)

STANDARD 000001-08

Illinois Department of Transportation

PASSED January 1, 2021
Michael Bond
ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021
Scott C. Clark
ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

Urban LT & RT Turn Arrow

Urban Thru Arrow

PAVEMENT MARKINGS
(contd.)

EX

PR

Urban U-Turn



Urban Combined U-Turn



Rural Combination Left



Rural Combination Right




Rural Left Turn Arrow



Rural Right Turn Arrow




Rural Left Turn Only





ONLY ONLY ONLY



Rural Right Turn Only



Rural Thru Only




Rural Thru Arrow



Rural Lt & Rt Turn Arrow



Bike Lane Symbol



Bike Lane Text



Bike Path Shared



Bike Shared Roadway



Lane Drop Symbol



Wrong Way Arrow

Illinois Department of Transportation
 PASSED January 1, 2021

 ENGINEER OF POLICY AND PROCEDURES
 APPROVED January 1, 2021

 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

**STANDARD SYMBOLS,
 ABBREVIATIONS
 AND PATTERNS**
(Sheet 6 of 9)
STANDARD 000001-08

RIGHT OF WAY ITEMS
(contd.)

| | EX | PR |
|--------------------------------------|------------|----------------|
| Access Control Line | — | — AC — |
| Access Control Line & ROW | — AC — | — AC — |
| Access Control Line & ROW with Fence | — x — AC — | — x — AC — x — |
| Excess ROW Line | | — XS — |

ROADWAY PLAN
ITEMS

| | EX | PR |
|--|-----------|------------|
| Cable Barrier | | |
| Concrete Barrier | | |
| Edge of Pavement | --- | --- |
| Bit Shoulders, Medians and C&G Line | --- | --- |
| Aggregate Shoulder | --- | --- |
| Sidewalks, Driveways | --- | --- |
| Guardrail | | |
| Guardrail Post | □ | □ |
| Traffic Sign | | |
| Corrugated Median | | |
| Impact Attenuator | | |
| North Arrow with District Office (Half Size) | | |
| Match Line | | STA. 45+00 |
| Slope Limit Line | --- | |
| Typical Cross-Section Line | --- | --- |

ROADWAY PROFILES

| | EX | PR |
|--------------------------------|-------------------------------|-------------------------------|
| P.I. Indicator | △ | △ |
| Point Indicator | ○ | ○ |
| Earthworks Balance Point | | |
| Begin Point | | |
| Vert. Curve Data | VPI = ELEV = L = E = | VPI = ELEV = L = E = |
| Ditch Profile Left Side | ---- | ---- |
| Ditch Profile Right Side | ---- | ---- |
| Roadway Profile Line | ---- | ---- |
| Storm Sewer Profile Left Side | ---- | ---- |
| Storm Sewer Profile Right Side | ---- | ---- |

SIGNING ITEMS

| | EX | PR |
|--------------------------|-----------|-----------|
| Cone, Drum or Barricade | | ○ |
| Barricade Type II | | |
| Barricade Type III | | TT |
| Barricade With Edge Line | | |
| Flashing Light Sign | | ○ |
| Panels I | | |
| Panels II | | |
| Direction of Traffic | | |
| Sign Flag (Half Size) | | |

SIGNING ITEMS
(contd.)

| | EX | PR |
|---|-----------|-----------|
| Reverse Left W1-4L (Half Size) | | |
| Reverse Right W1-4R (Half Size) | | |
| Two Way Traffic Sign W6-3 (Half Size) | | |
| Detour Ahead W20-2(O) (Half Size) | | |
| Left Lane Closed Ahead W20-5L(O) (Half Size) | | |
| Right Lane Closed Ahead W20-5R(O) (Half Size) | | |
| Road Closed Ahead W20-3(O) (Half Size) | | |
| Road Construction Ahead W20-1(O) (Half Size) | | |
| Single Lane Ahead (Half Size) | | |
| Transition Left W4-2L (Half Size) | | |
| Transition Right W4-2R (Half Size) | | |

Illinois Department of Transportation

PASSED January 1, 2021
Michael Bond
ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021
Joe E. Cole
ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

**STANDARD SYMBOLS,
ABBREVIATIONS
AND PATTERNS**
(Sheet 7 of 9)


STANDARD 000001-08

SIGNING ITEMS
(contd.)


EX

PR

One Way Arrow Lrg. W1-6-(O)
(Half Size)



Two Way Arrow Large W1-7-(O)
(Half Size)



Detour M4-10L-(O)
(Half Size)



Detour M4-10R-(O)
(Half Size)



One Way Left R6-1L
(Half Size)



One Way Right R6-1R
(Half Size)



Left Turn Lane R3-I100L
(Half Size)



Keep Left R4-7AL
(Half Size)



Keep Left R4-7BL
(Half Size)



Keep Right R4-7AR
(Half Size)



Keep Right R4-7BR
(Half Size)



Stop Here On Red R10-6-AL
(Half Size)



Stop Here On Red R10-6-AR
(Half Size)




No Left Turn R3-2
(Half Size)




No Right Turn R3-1
(Half Size)



Road Closed R11-2
(Half Size)



Road Closed Thru Traffic R11-2
(Half Size)




STRUCTURES ITEMS

EX

PR


Box Culvert Barrel



Box Culvert Headwall




Bridge Pier



Bridge



Retaining Wall



Temporary Sheet Piling



TRAFFIC SHEET
ITEMS

EX

PR

Cable Number




Left Turn Green



Left Turn Yellow



Signal Backplate



Signal Section 8" (200 mm)



Signal Section 12" (300 mm)



Walk/Don't Walk Letters



Walk/Don't Walk Symbols



TRAFFIC SIGNAL
ITEMS

EX

PR

Galv. Steel Conduit



Underground Cable



Detector Loop Line



Detector Loop Large



Detector Loop Small



Detector Loop Quadrapole



STANDARD SYMBOLS,
ABBREVIATIONS
AND PATTERNS

(Sheet 8 of 9)

STANDARD 000001-08

Illinois Department of Transportation

PASSED January 1, 2021
Michael Bond
ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2021
Joe E. Cole
ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

TRAFFIC SIGNAL ITEMS (contd.)

EX

PR

| | | |
|--------------------------|--|--|
| Detector Raceway | | |
| Aluminum Mast Arm | | |
| Steel Mast Arm | | |
| Veh. Detector Magnetic | | |
| Conduit Splice | | |
| Controller | | |
| Gulfbox Junction | | |
| Wood Pole | | |
| Temp. Signal Head | | |
| Handhole | | |
| Double Handhole | | |
| Heavy Duty Handhole | | |
| Junction Box | | |
| Ped. Pushbutton Detector | | |
| Ped. Signal Head | | |
| Power Pole Service | | |
| Priority Veh. Detector | | |
| Signal Head | | |
| Signal Head w/Backplate | | |
| Signal Post | | |
| Closed Circuit TV | | |
| Video Detector System | | |

UNDERGROUND UTILITY ITEMS

EX

PR

ABANDONED

| | | | |
|-----------------|--|--|--|
| Cable TV | | | |
| Electric Cable | | | |
| Fiber Optic | | | |
| Gas Pipe | | | |
| Oil Pipe | | | |
| Sanitary Sewer | | | |
| Telephone Cable | | | |
| Water Pipe | | | |

UTILITIES ITEMS

EX

PR

| | | |
|-----------------------------------|--|--|
| Controller | | |
| Double Handhole | | |
| Fire Hydrant | | |
| GuyWire or Deadman Anchor | | |
| Handhole | | |
| Heavy Duty Handhole | | |
| Junction Box | | |
| Light Pole | | |
| Manhole | | |
| Monitoring Well (Gasoline) | | |
| Pipeline Warning Sign | | |
| Power Pole | | |
| Power Pole with Light | | |
| Sanitary Sewer Cleanout | | |
| Splice Box Above Ground | | |
| Telephone Splice Box Above Ground | | |
| Telephone Pole | | |

UTILITY ITEMS (contd.)

EX

PR

| | | |
|----------------------------|--|--|
| Traffic Signal | | |
| Traffic Signal Control Box | | |
| Water Meter | | |
| Water Meter Valve Box | | |
| Profile Line | | |
| Aerial Power Line | | |

VEGETATION ITEMS

EX

PR

| | |
|----------------------|--|
| Deciduous Tree | |
| Bush or Shrub | |
| Evergreen Tree | |
| Stump | |
| Orchard/Nursery Line | |
| Vegetation Line | |
| Woods & Bush Line | |

WATER FEATURE ITEMS

EX

PR

| | |
|--------------------------|--|
| Stream or Drainage Ditch | |
| Waters Edge | |
| Water Surface Indicator | |
| Water Point | |
| Disappearing Ditch | |
| Marsh | |
| Marsh/Swamp Boundary | |

Illinois Department of Transportation

PASSED January 1, 2021

 ENGINEER OF POLICY AND PROCEDURES




ISSUED 1-1-97

APPROVED January 1, 2021

 ENGINEER OF DESIGN AND ENVIRONMENT

STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
 (Sheet 9 of 9)

STANDARD 000001-08



TYPICAL APPLICATIONS

- Marking patches
- Field survey
- String line
- Utility operations
- Cleaning up debris on pavement

SYMBOLS

- Work area
- Sign on portable or permanent support
- Flagger with traffic control sign

All dimensions are in inches (millimeters) unless otherwise shown.

Illinois Department of Transportation

PASSED January 1, 2011
Amelia Adams
 ENGINEER OF SAFETY ENGINEERING


APPROVED January 1, 2011
Scott Schick
 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97

| DATE | REVISIONS |
|--------|-------------------------------------|
| 1-1-11 | Revised flagger sign. |
| 1-1-09 | Switched units to English (metric). |

LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

STANDARD 701301-04



| SIGN SPACING | |
|--------------|--------------|
| Posted Speed | Sign Spacing |
| 55 | 500' (150 m) |
| 50-45 | 350' (100 m) |
| <45 | 200' (60 m) |

SYMBOLS

- Work area
- Cone, drum or barricade (not required for moving operations)
- Sign on portable or permanent support
- Flagger with traffic control sign
- Barricade or drum with flashing light
- Type III barricade with flashing lights

- ① Refer to SIGN SPACING TABLE for distances.
- ② For approved sideroad closures.
- ③ Cones at 25' (8 m) centers for 250' (75 m). Additional cones may be placed at 50' (15 m) centers. When drums or Type I or Type II barricades are used, the interval between devices may be doubled.
- ④ Cones, drums or barricades at 20' (6 m) centers.

GENERAL NOTES

This Standard is used where at any time, day or night, any vehicle, equipment, workers or their activities encroach on the pavement requiring the closure of one traffic lane in an urban area.

All dimensions are in inches (millimeters) unless otherwise shown.

Illinois Department of Transportation

PASSED January 1, 2011
[Signature]
 ENGINEER OF SAFETY ENGINEERING


APPROVED January 1, 2011
[Signature]
 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-97


| DATE | REVISIONS |
|--------|-------------------------------------|
| 1-1-11 | Revised flagger sign. |
| 1-1-09 | Switched units to English (metric). |
| | Corrected sign No.'s. |

**URBAN LANE CLOSURE,
2L, 2W, UNDIVIDED**


STANDARD 701501-06




DAYTIME USE




DAY OR NIGHTTIME USE



TUBULAR MARKER




**VERTICAL PANEL
POST MOUNTED**




DRUM


CONES




TYPE I BARRICADE




TYPE II BARRICADE




TYPE III BARRICADE



**DIRECTION INDICATOR
BARRICADE**



VERTICAL BARRICADE



**DETECTABLE PEDESTRIAN
CHANNELIZING BARRICADE**

* Warning lights (if required)

GENERAL NOTES

All heights shown shall be measured above the pavement surface.

All dimensions are in inches (millimeters) unless otherwise shown.

| DATE | REVISIONS |
|--------|---|
| 1-1-19 | Revised cone usage and added cones >36" (900 mm) height. |
| 1-1-18 | Revised END WORK ZONE SPEED LIMIT sign from orange to white background. |

TRAFFIC CONTROL DEVICES

(Sheet 1 of 3)

STANDARD 701901-08

Illinois Department of Transportation


APPROVED January 1, 2019

 ENGINEER OF SAFETY PROG. AND ENGINEERING

APPROVED January 1, 2019


 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED
 ET-1-1




POST MOUNTED SIGNS

** When curb or paved shoulder are present this dimension shall be 24 (600) to the face of curb or 6' (1.8 m) to the outside edge of the paved shoulder.



SIGNS ON TEMPORARY SUPPORTS

*** When work operations exceed four days, this dimension shall be 5' (1.5 m) min. If located behind other devices, the height shall be sufficient to be seen completely above the devices.




HIGH LEVEL WARNING DEVICE

| | |
|--------------------------------|------------------|
| ROAD CONSTRUCTION NEXT X MILES | END CONSTRUCTION |
| G20-I104(0)-6036 | G20-I105(0)-6024 |

This signing is required for all projects 2 miles (3200 m) or more in length.
 ROAD CONSTRUCTION NEXT X MILES sign shall be placed 500' (150 m) in advance of project limits.
 END CONSTRUCTION sign shall be erected at the end of the job unless another job is within 2 miles (3200 m).
 Dual sign displays shall be utilized on multi-lane highways.


WORK LIMIT SIGNING



W12-I103-4848

WIDTH RESTRICTION SIGN

XX'-XX" width and X miles are variable.



FRONT SIDE

REVERSE SIDE

FLAGGER TRAFFIC CONTROL SIGN

| | |
|--------------------|---------------------|
| WORK ZONE | W21-III5(0)-3618 |
| SPEED LIMIT XX | R2-1-3648 |
| PHOTO ENFORCED | R10-I108p-3618 **** |
| \$XXX FINE MINIMUM | R2-I106p-3618 |

Sign assembly as shown on Standards or as allowed by District Operations.

| | |
|---------------------------|---------------|
| END WORK ZONE SPEED LIMIT | G20-I103-6036 |
|---------------------------|---------------|

This sign shall be used when the above sign assembly is used.

HIGHWAY CONSTRUCTION SPEED ZONE SIGNS

**** R10-I108p shall only be used along roadways under the jurisdiction of the State.

Illinois Department of Transportation

APPROVED January 1, 2019
[Signature]
 ENGINEER OF SAFETY PROG. AND ENGINEERING


APPROVED January 1, 2019
[Signature]
 ENGINEER OF DESIGN AND ENVIRONMENT

ISSUED 1-1-13





TRAFFIC CONTROL DEVICES

(Sheet 2 of 3)


STANDARD 701901-08



ARROW BOARDS




TEMPORARY RUMBLE STRIPS



ROAD CLOSED TO ALL TRAFFIC

Reflectorized striping may be omitted on the back side of the barricades. If a Type III barricade with an attached sign panel which meets NCHRP 350 is not available, the sign may be mounted on an NCHRP 350 temporary sign support directly in front of the barricade.



ROAD CLOSED TO THRU TRAFFIC

Reflectorized striping shall appear on both sides of the barricades. If a Type III barricade with an attached sign panel which meets NCHRP 350 is not available, the signs may be mounted on NCHRP 350 temporary sign supports directly in front of the barricade.

TYPICAL APPLICATIONS OF TYPE III BARRICADES CLOSING A ROAD

TRAFFIC CONTROL DEVICES

(Sheet 3 of 3)

STANDARD 701901-08

Illinois Department of Transportation

APPROVED January 1, 2019

Cynthia Watt
ENGINEER OF SAFETY PROG. AND ENGINEERING

APPROVED January 1, 2019

Joe E. ...
ENGINEER OF DESIGN AND ENVIRONMENT

ISSUES: E1-1-1 Q3581